



ELECTROMECHANICAL LUBRICATOR



THE EFFICIENT AND ECONOMIC SOLUTION FOR SINGLE LUBRICATION POINTS

- Electromechanical drive
- 10 bar (145 psi)
- Up to 24 months per filling
- Refillable up to 5 times without any follow-up costs
*total 720ml or a maximum of 48 months
- self-filling possible
- Oil or grease up to NLGI cl. 2
- - 20 °C bis + 60°C
* with suitable lubricant

„Easy filling“

LUB 5 can be filled easily
and quickly by a
grease gun



**AUTOMATIC LUBRICATION OF
BEARINGS, CHAINS, OPEN TOOTH
SYSTEMS AND LINEAR MOTIONS**








Runtime

LUB 5 is running 24 months per filling

The running time per filling is adjusted directly on the device.
The remaining filling cycles are shown by LEDs.

**Technical
Data**

Lubricant volume :	120 ml (refillable)
Discharges:	Up to 6 = 720 ml (or a max. of 48 Months)
Lubricant:	Oil or grease up to NLGI cl. 2
Diameter / height:	70 mm/127mm
Runtime per filling:	1 / 3 / 6 / 12 / 24 months
Fixing thread:	External thread R1/4
Filling:	Standard lubricant or available empty

<p>UP TO 24 MONTHS</p>	<p>OPERATING PRESSURE 10 BAR</p>	<p>MAX 48 MONTH LIFETIME</p>	<p>REFILL  5x</p>
<p>LED  DISPLAY</p>	<p>MOUNTING  IN ANY POSITION</p>	<p>MICRO CONTROLLER </p>	<p>BATTERY POWERED </p>



Gruetzner
GmbH
Kohlenhofstr. 60
D - 90443 Nürnberg



Tel. +49 (0)911 277 399 0
Fax. +49 (0)911 277 399 99
Mail. info@lub5.com

WWW.LUB5.COM

